

SECLUSION ROOM LOCKSETS

Unsupervised – Key Operated

Code compliance to be confirmed prior to specification and use

Multi-Point Deadbolt Mortise Lock

Key-activated 3-point lock - Key required for operation; Special door prep required



Model Information

UML-K3-IHB2

3-Point Deadbolt Lockset

Key projection/retraction
Exterior operation only
Free-moving anti-ligature lever trim
Trim does not retract bolts

LOCK INFO

Mortise lockset with primary horizontal deadbolt, top vertical deadbolt and lower horizontal deadbolt module.

TRIM INFO

Anti-ligature lever provided for use as door pull. Anti-ligature lever is fastened to trim plate which is held to door with jacknuts (thru-bolted on wood doors).

CYLINDER INFO

Mortise cylinder required for operation.

DOOR INFO

Designed for hollow metal doors with factory preparation.

May be used on wood doors with factory preparation. Lower module access plate (can be installed on exterior side of door) required for wood door models.

OPERATION

The exterior cylinder retracts or projects all deadbolts in one motion. There is no interior door hardware.

The anti-ligature trim is used as a door pull. It is free-moving at all times. It has no connection to the lock body and will not retract the deadbolts.



Note: A Typical Seclusion Room Door Does Not Have Interior Trim.

Multi-point locking has proven effective against violent attempts to force the door open.

Securitech offers a wide-range of multi-point locks for use in supervised and unsupervised seclusion and time-out rooms.

Other Models



UMP-K3-IHB2
Traditional pull trim

UMX-K3-IHB2
No exterior trim (cylinder only)

Interior trim is not recommended within seclusion rooms.

GENERAL INFORMATION

DOOR TYPE: 18 gauge or heavier vertically-stiffened hollow metal, recommended. Wood & others may be used with vertical rod preps.

DOOR & FRAME PREPARATION: Mortise lock preparation required for lock body. Flush bolt prep required for HVL module. Inverted U-Channel used for vertical deadbolts.

HANDED: Order LH, LHR, RH Or RHR (for lever preparation).

SIZE: Shipped Standard For 3'x7' Door. Can Be Field Cut For Smaller Doors. Specify Taller Size When Ordering.

DOOR THICKNESS: Designed For 1-3/4" Doors. Specify Thicker When Ordering.

CYLINDER: Mortise Cylinder, Cloverleaf Cam. Contact Factory With Cylinder Information For Cam Info.