

## SECLUSION ROOM LOCKSETS

*Unsupervised – Key Operated*

**Special “Slam” Lock Function: Code compliance to be confirmed prior to specification and use**

### Multi-Point Deadbolt Mortise “Slam” Lock



*Note: A Typical Seclusion Room Door Has A Vision Lite*

**Key-activated 3-point lock with latch**  
**Door latches shut each time it closes.**  
**Key required for entry at all times and deadbolt operation;**  
**Special door prep required**

### Model Information

#### USL-K3-IHB2

#### 3-Point Deadbolt & Latch Lockset

Key projection/retraction  
Cylinder operation possible from both sides (interior operation is recommended, but optional)  
Free-moving anti-ligature lever trim  
Trim does not retract bolts

#### LOCK INFO

Mortise lockset with primary horizontal deadbolt, top vertical deadbolt and lower horizontal deadbolt module.

#### TRIM INFO

Anti-ligature lever provided for use as door pull. Anti-ligature lever is fastened to trim plate which is held to door with jacknuts (thru-bolted on wood doors).

#### CYLINDER INFO

Mortise cylinder required for operation.

#### DOOR INFO

Designed for hollow metal doors with factory preparation.

May be used on wood doors with factory preparation. Lower module access plate (can be installed on exterior side of door) required for wood door models.

#### OPERATION

The cylinder(s) retracts or projects all deadbolts in one motion. The latch is then retracted by the cylinder(s).

The anti-ligature trim is used as a door pull. It is free-moving at all times. It has no connection to the lock body and will not retract the deadbolts or latch.



### Other Models



**USP-K3-IHB2**  
Traditional pull trim

**USX-K3-IHB2**  
No exterior trim (cylinder only)

Interior trim is not recommended within seclusion rooms, but cylinder is recommended for USL models.

**Multi-point locking has proven effective against violent attempts to force the door open.**

Securitech offers a wide-range of multi-point locks for use in supervised and unsupervised seclusion and time-out rooms.

### GENERAL INFORMATION

**DOOR TYPE:** 18 gauge or heavier vertically-stiffened hollow metal, recommended. Wood & others may be used with vertical rod preps.

**DOOR & FRAME PREPARATION:** Mortise lock preparation required for lock body. Flush bolt prep required for HVL module. Inverted U-Channel used for vertical deadbolts.

**HANDED:** Order LH, LHR, RH Or RHR (for lever preparation).

**SIZE:** Shipped Standard For 3'x7' Door. Can Be Field Cut For Smaller Doors. Specify Taller Size When Ordering.

**DOOR THICKNESS:** Designed For 1-3/4" Doors. Specify Thicker When Ordering.

**CYLINDER:** Mortise Cylinder, Cloverleaf Cam. Contact Factory With Cylinder Information For Cam Info.