

**TIME-LOCK
EXIT DEVICE
& CONTROLLER**

USPS-TL-FA Series

**Push-Pull Door Operation
During Open Hours**

* * *

Automatic Locking & Unlocking

USPSTL-FA-200 has been designed to meet the special locking and durability needs of the US Postal Service. The exit device features electric latch retraction for unmanned automatic unlocking and locking of the door. A field programmable timer, secured in a locked enclosure, is used to create time zones, programmable by day of the week.

Life-safety codes are respected via the single motion panic bar which is operable at all times, even if a customer is within the station when the door automatically locks. Exiting is always possible. Entry is possible by key during locked periods.

Exit Device:

- o Designed For High Traffic Locations
- o ANSI Grade 1, UL Listed
- o Electric Latch Retraction
- o Heavy Duty, 24vDC Solenoids Suitable For High Traffic Conditions And Capable Of Extended Periods Of Activation
- o Keyed Entry (Cylinder By Others)
- o 1" Forged Steel Latch Bolt
- o High-Performance Anodized Coatings
- o Solid Metal End Clips
- o Can Be Mounted On 2" Narrow Stile Doors
- o Available For Doors Up To 4' Wide
- o Non-handed

Power Supply:

- o UL Listed For Access Control Systems (UL294), CUL Listed - CSA Standard C22.2 No.205-M1983, Signal Equipment.
- o Input 115VAC 50/60Hz, 1 Amp
- o Designed Specifically To Operate USPS-TL Exit Device

Timer:

- o 365 Day 24 Hr Annual Event Timer
- o Field Programmable
- o Alphanumeric LCD Display Simplifies Programming
- o Standard Or Daylight Savings Time Settings
- o Automatic Compensation For Leap Year
- o Key Lockable Enclosure



Exit device shown with latch electrically held-back



Exit device can be retrofit to a wide variety of door types and can be used with automatic openers



Power Supply & Timer Supplied connected via armored cable for easy installation

made in usa by SECURITECH GROUP, INC.
54-60 46th St. Maspeth, NY 11378
800.622.5625 718.392.9000 718.392.8944 fax
www.securitech.com

*Model numbers & elements***#USPS-TL-FA-200**

Designed for use on wood, steel and wide-stile aluminum doors

Includes:

Latch Retraction Exit Device with connector
Wire Harness (to run through door)
Strike plate (for single door opening)
Power Transfer Loop
Controller
Timer (connected to controller via armored cable)



Standard Exit Device

#USPS-TL-FA-201

Designed for use on 36" wide narrow-stile aluminum doors (notify if door width differs)
May be used on any door (check door width)

Includes:

All USPS-TL-FA-200 items
Steel mounting plate
Factory mounting of exit device on plate



Exit Device On Mounting Plate

Required by others:
Rim Cylinder

Installation Information:
Review instructions for door and electrical requirements. 110v required for Controller

Programming:
Field time zone programming required

Designed for outswing doors
Non-Handed

Options:
USPS-TL-DDS Strike for use on double doors